MOBILTEX

FloPath® TRID

DISPLAY PRESSURE/FLOW DATA LOGGER ENGINEERED FOR EXTREME CONDITIONS

FloPath
a MOBILTEX brand



Product may not ship exactly as shown

FLEXIBLE AND COST EFFECTIVE DATA LOGGER WITH CUSTOMIZABLE DISPLAY — WATERPROOF AND SUBMERSIBLE WITH LONG-LIFE BATTERY POWER.

The TRID range of data loggers use a new data logging architecture that allows the user to monitor pressure/flow inputs in a multitude of configurations providing ultimate flexibility to meet specific application requirements.

The FloPath TRID stores data in non-volatile memory organized into data files. Each data file is an independent data logger with its own start/stop time, sample rate and logging rate. More than one data file can record different types of data for the same input channel. Different types of data include Average, Instantaneous, Minimum, Maximum etc. The memory register size is designed to be ready to accommodate overflows associated with high pulse rates on Flow inputs.

Pressure measurement accuracy is optimized using multi point calibration. Logged data can be re-calibrated before, during or after the recording by recalibrating the pressure transducer to the logger.

Local communications is via a fast non-contact IrDA communications link (115,200 baud). The logger firmware can also be upgraded in the field via the IrDA communications link.

FEATURES OF FLOPATH TRID

- One, two, three and four channel models with up to two pressure sensors
- 2 MB Flash non-volatile memory organized into 6 separate data files - 60000 reading each and 2 separate data files - 250000 readings each
- Data is retained for 10 years if battery power fails.
- Sampling Rate: Configurable 1 second to 15 minutes
- Logging Rate: Configurable 5 seconds to 24 hours
- Logged Data Types: Average, Instantaneous, Minimum, Maximum
- Flow Logging Modes: Count, Event, Pulse Interval Timing
- Communications: IrDA – Baud Rate of 115,200 Baud
- Completely waterproof and submersible (IP68)
- Stainless steel, fully potted case - unmatched durability
- Battery life > 5 years under normal operation



FLOPATH TRID APPLICATIONS:

- LEAKAGE FLOW-MONITORING
- PRESSURE ZONE / DMA BOUNDARY VALVE MONITORING
- PRESSURE/PRV MONITORING
- HYDRAULIC NETWORK ANALYSIS
- PRESSURE SURGE DETECTION
- CUSTOMER PRESSURE COMPLAINT INVESTIGATIONS
- RAINFALL MONITORING
- PUMP ON/OFF TIMES
- MINIMUM NIGHT FLOW ANALYSIS

TRID SPECIFICATIONS

LOGGING | COMMUNICATIONS | DATA:

Memory:	2 MB Flash non-volatile memory organized into 6 separate data files - 60000 reading each and 2 separate data files - 250000 readings each Block or Cyclic – Start/Stop
Memory Type:	Flash non-volatile memory. Data is retained for 10 years if battery power fails.
Sampling Rate:	Configurable: 1 second to 15 minutes
Logging Rate:	Configurable: 5 second to 24 hours
Logged Data Types:	Average, Instantaneous, Minimum, Maximum
Flow Logging Modes:	Count, Event, Pulse Interval Timing
Communications:	IrDA – Baud Rate of 115,200 Baud
Logger range:	1 to 4 channels selectable from 2-Flow and 2-Pressure/Analogue
LCD Display:	8-Digit Display: User configurable display units, latest data values & summary

ANALOG & DIGITAL INPUTS:

Pressure transducers:	20 Bar / 290 psi Range Standard
Pulse Rate:	Std. 80/second - Max 400/second optional
Flow Meter Sensors:	Compatible with all major meter manufacturers that are equipped with a digital pulse output.

PHYSICAL | POWER | ENVIRONMENTAL:

Case Dimensions:	145mm L x 90mm W x 55mm D
Enclosure:	Stainless Steel - Powder Coated
Weight:	1.25 kg
Battery:	>5 years depending on model/settings
Operating Temperature:	-20 to 70 °C [-5 to 160 °F]
Ingress Rating:	IP68 Submersible

ORDERING MATRIX:

PARAMETER	OPTIONS	CODE
Enclosure Type	Stainless Steel	TRID
Pressure Sensors	One Internal Pressure	P
	Two Internal Pressure	PP
	None	
Flow Logging	One Flow	F
	TWO FLOW	FF
	NONE	

EXAMPLE :

Display Portable logger with two internal pressure, one flow input = TRID-PPF

OPTIONAL COMPONENTS	PART #
Flow Input Cable	GA1
Coiled Pressure Hoses	CHP
Female Quick Release	QFF
Programming Cable	COM1-25

Authorized Reseller

MOBILTEX-FloPath-TRID-BRO-0225



MORE QUESTIONS?
WE'VE GOT ANSWERS!

+1.844.689.3282 (844.MTX.DATA) | info@mobiltex.com | mobiltex.com

MOBILTEX® and FloPath® are registered trademarks of MOBILTEX Data Ltd. Subject to change without notice. All rights reserved.